



ALUMINIUM WINDOW & DOOR STANDARD COLOUR RANGE

STANDARD COLOURS



THERMALHEART® DUAL FINISH TECHNOLOGY

In order to acheive excellent thermal performance, ThermalHEART® systems incorporate an innovative polyamide insulator strip which separates the internal and external elements of the extrusion and drastically improves insulation against radiant heat and cold transfer between the internal and external environments.

The innovative thermal insulator joining method allows a different choice of finish to complement both internal and external finish palettes resulting in one finish on the outside and another on the inside.



Single Finish

Where you desire the same finish for your joinery inside and out, select from any of the finishes



Dual Finish

If you would like to utilise different finishes on the inside and outside of your joinery, select an external colour, and then a corresponding internal colour.

The delivery time and cost of the finishes available in this finish card will vary depending on your choice. Please obtain a comprehensive quote from your Vantage or Elevate fabricator prior to placing your order. Finishes displayed on this finish card are a guide only and have been matched as close as possible to production standards under daylight conditions. Over time performance may vary between COLORBOND® steel and powder coated Vanatage or Elevate joinery due to the different paint technologies used.

CHOOSING A COLOUR FOR YOUR WINDOW AND DOOR SYSTEMS REQUIRES CAREFUL THOUGHT. ALL VANTAGE, ELEVATE™ AND THERMALHEART® WINDOWS AND DOORS ARE MADE TO ORDER SO YOU HAVE COMPLETE FREEDOM TO CHOOSE THE PERFECT COLOUR AND FINISH FOR YOUR PROJECT.

WARRANTIES

The finish on Vantage and Elevate™ Joinery is supplied by market leaders Dulux Powder Coatings. AWS offers comprehensive warranties on the finish of your Vantage and Elevate™ joinery for your peace of mind.

Depending on your colour choice, you will benefit from warranty cover ranging from a minimum of 7 years film integrity and 7 years colour integrity for residential applications, and up to 15 years film integrity and 15 years colour integrity for high-end residential and commercial applications. Please consult your AWS fabricator to obtain details of the warranty terms and conditions or to view a sample warranty.

CARE AND MAINTENANCE

Like any other painted surface, powder coated aluminium performs at its best when it is properly cared for. Keeping the surface free from pollutants and environmental contaminants will give you the maximum benefit and long-lasting performance from your powder coated surface.

RECOMMENDED CLEANING

A gentle clean with a soft brush and mild detergent, followed by a fresh water rinse, will maintain the long-term performance of your powder coated products. In rural or normal urban environments, cleaning should occur every 12 months. In areas of high pollution, such as industrial areas or coastal environments, cleaning should occur every three months. In particularly hazardous locations such as beachfronts, severe marine environments or areas of high industrial pollution, cleaning should occur monthly. Do not use strong solvents, abrasive cleaning products or any product recommended for thinning paints. If you need to remove splashed paint, sealants or mastics from your powder coated products use white spirits. Carry out cleaning in shade and during cooler temperatures using a soft cloth and gentle wiping only.

We recommend that prior to using any cleaning agent on your windows or doors, you test a small non-visible area of your powder coated product to ensure that no visual colour change or damage will occur. Ask your fabricator for the care and maintenance information specific to your product choice.

Queanbeyan Showroom

Unit 8/42 Stephens Road Ph: (02) 6299 1515 Fax: (02) 6299 1464 info@monarowindows.com.au Mitchell Showroom

5/5 Pelle St Mitchell Ph: (02) 6241 0999 Fax: (02) 6241 0977 info@monarowindows.com.au monarowindows.com.au

